

ECO.40/2

Magnetic drilling machine

 **EUROBOOR**

FOR PROFESSIONALS BY PROFESSIONALS

Technical data

	Metric	Imperial
Annular cutting	Ø 12 - 40 mm	Ø 1/2" - 1 9/16"
Twist drilling	Ø 1 - 13 mm	Ø 1/16" - 1/2"
Countersinking	Ø 10 - 45 mm	Ø 3/8" - 1 3/4"
Length	320 mm	12 5/8"
Width	210 mm	8 1/4"
Height	395 - 540 mm	15 9/16" - 21 1/4"
Stroke	150 mm	5 15/16"
Weight*	11.5 kg	25.4 lbs
Magnet (l x w x h)	160 x 80 x 42 mm	6 5/16" x 3 1/8" x 1 5/8"
Magnetic force	1,500 kg	3,305 lbs
Motor power	1,050 W	9.5 A
Total power	1,100 W	10 A
Speed		(I) 720 rpm
(no load)		(II) 1,300 rpm
Speed		(I) 315 rpm
(load 1,050 W, 9.5 A)		(II) 560 rpm
Spindle (Weldon)	19.05 mm	3/4"
Voltage		110 - 120 V / 60 Hz
		220 - 240 V / 50 - 60 Hz

* Without power cord and handles

Features



**Magnet
LED-indicator
(SensorTec)**



Euroboor makes every effort to meet quality and integrity requirements. That is why we as an organization are proud of the recognition of some leading organizations worldwide:



www.euroboor.com