

Material Safety Data Sheet

PST.5000

Trade name: EUROBOOR PST.5000

Date: 01-02-2026

Version: 1.0

Report Number:1811C50409412701

SECTION 1: Identification of the product and of the company/ undertaking

1.1 Product identifier

Professional Portable Power Station PST.5000

1.2 Product information

Product name: PST.5000

Product description: Portable Power Station

Battery type: Ternary Lithium Ion battery cell

Battery voltage: DC 51.2V

Battery capacity: 5,120 Wh

Rated output power: max. 100Ah

Rated output voltage: AC 220 V 50 Hz / DC 20V 5A

1.3 Details of the supplier of the safety data sheet supplier

Euroboor BV

Kryptonstraat 110,
2718 TD Zoetermeer

The Netherlands

info@euroboor.com

www.euroboor.com

1.4 Emergency telephone number

+31 (0)79 3614990 - Central European Time 08:30 - 17:00 hrs

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Acute toxicity - Oral, Category 3

Skin corrosion, Category 1A

Serious eye damage, Category 1

Specific target organ toxicity – repeated exposure, Category 1

Material Safety Data Sheet

PST.5000

2.2 GHS label elements, including precautionary statements:

Pictogram:



Signal word: Danger

Hazard statements:

H301 Toxic if swallowed

H314 Causes severe skin burns and eye damage

H372 Causes damage to organs through prolonged or repeated exposure

H361 Suspected of damaging fertility or the unborn child

Precaution statements:

Prevention

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301+P310 IF SWALLOWED: Immediately call a doctor.

P321 Specific treatment.

P330 Rinse mouth.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P363 Wash contaminated clothing before use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310 Immediately call a doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container to ...

Supplemental Hazard:

none

Material Safety Data Sheet

PST.5000

SECTION 3: Composition/information on ingredients

Chemical composition	CAS No.	Weight (%)
LiFePo4	15365-14-7	24%
LiPF6	21324-40-3	23%
Al	7429-90-5	5%-10%
C	7782-42-5	10%-30%
Cu	7440-50-8	7%-13%
Ni	7440-02-0	1%-5%

SECTION 4: First-aid measures

General Advice

The chemicals and metals in this product are contained in a sealed can. Exposure to the contents will not occur unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused.

Eyes

If battery is leaking and material contacts the eye, flush thoroughly with copious amounts of running water for 30 minutes. Seek immediate medical advice.

Skin

If battery is leaking and material contacts the skin, remove any contaminated clothing and flush exposed skin with copious amounts of running water for at least 15 minutes. If irritation, injury or pain persists, seek medical advice.

Inhaled

If battery is leaking, contents may be irritating to respiratory passages. Move to fresh air. If irritation persists, seek medical advice.

Swallowed

If battery is swallowed seek immediate medical advice. Batteries lodged in the esophagus should be removed immediately since leakage, caustic burns and perforation can occur as soon as two hours after ingestion. If mouth area irritation or burning has occurred, rinse the mouth and surrounding area with tepid water for at least 15 minutes. Do not vomit.

Material Safety Data Sheet

PST.5000



SECTION 5: Firefighting measures

Fire and explosion hazards

Batteries may burst and release hazardous decomposition products when exposed to a fire situation.

Extinguishing Media

Use any extinguishing media that is appropriate for the surrounding fire.

Special Fire Fighting Procedures

Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Fight fire from a distance or protected area. Cool fire exposed batteries to prevent rupture. Use caution when handling fire-exposed containers (batteries may explode in heat of fire).

Hazardous Combustion Products

Thermal degradation may produce hazardous fumes of lithium and manganese; hydrofluoric acid, oxides of carbon and sulfur and other toxic by-products.

SECTION 6: Accidental release measures

Notify safety personnel of large spills. Irritating vapors and flammable may be released from leaking or ruptured batteries. Eliminate all ignition sources. Evacuate the area and allow the vapors to dissipate. Clean-up personnel should wear appropriate protective clothing to avoid eye and skin contact and inhalation of vapors or fumes. Increase ventilation. Carefully collect batteries and place in an appropriate container for disposal. Remove spilled liquid with absorbent and contain for disposal.

SECTION 7: Handling and storage

Handling

Avoid mechanical or electrical abuse. DO NOT short circuit or install incorrectly. Batteries may explode, pyrolyze or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions. Replace all batteries in equipment at the same time. Do not carry batteries loose in a pocket or bag.

Storage

Store batteries in a dry place at normal room temperature.

Material Safety Data Sheet

PST.5000



SECTION 8: Exposure control/Personal protection

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use.

Ventilation

Not necessary under conditions of normal use.

Other Protective clothing or equipment

Not necessary under conditions of normal use.

Personal Protection is recommended for venting battery

Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

SECTION 9: Physical and chemical properties

Appearance

--

Odour

--

Color

--

pH

Not applicable

Flash Point

Not applicable

Flammability

Not applicable

Relative density

Not applicable

Solubility (water)

Insoluble

Solubility (other)

Not applicable

Material Safety Data Sheet

PST.5000



SECTION 10: Stability and reactivity

Stability

This product is stable.

Incompatibility/Conditions to Avoid

Contents are incompatible with strong oxidizing agents. Do not heat, crush, disassemble, short circuit or recharge.

Hazardous Decomposition Products

Thermal decomposition may produce hazardous fumes of lithium and manganese; hydrofluoric acid, oxides of carbon and sulfur and other toxic by-products.

Hazardous Polymerization

Will not occur

SECTION 11: Toxicological information

Potential Health Effects

The chemicals and metals in this product are contained in a sealed can. Exposure to the contents will not occur unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused.

Eye Contact

Contact with battery contents may cause irritation.

Skin Contact

Contact with battery contents may cause irritation.

Inhalation

Inhalation of vapors or fumes released due to heat or a large number of leaking batteries may cause respiratory and eye irritation.

Ingestion

Swallowing is not anticipated for larger batteries due to battery size. Smaller batteries may be swallowed. If battery is swallowed, seek immediate medical advice. Batteries lodged in the esophagus should be removed immediately since leakage, caustic burns and perforation can occur as soon as two hours after ingestion. Irritation to the internal/external mouth areas, may occur following exposure to a leaking battery.

Chronic Effects

The chemicals in this product are contained in a sealed can and exposure does not occur during normal handling and use. No chronic effects would be expected from handling a leaking battery.

Target Organs

Skin, eyes and respiratory system.

Material Safety Data Sheet

PST.5000

Carcinogenicity

None of the components of this product are listed as carcinogens by the EU Directive on the classification and labeling of substances.

SECTION 12: Ecological information

When properly used and disposed this product does not present an environmental hazard.

The Battery does not contain mercury, cadmium or lead.

SECTION 13: Disposal

Do not incinerate or subject cells to temperature in excess of 80°C. Dispose of in accordance with local regulations.

SECTION 14: Transport information

All lithium, lithium ion and lithium polymer cells and batteries must be tested in accordance with the "UN Manual of Tests and Criteria, Part III, Subsection 38.3 2017.

The 64th edition of the IATA Dangerous Goods Regulations incorporates all amendments made by the ICAO Dangerous Goods Panel in developing the content of the 2021 edition of the ICAO Technical Instructions as well as changes adopted by the IATA Dangerous Goods Board. Their regulations are based on the UN Recommendations. The UN Recommendations require that lithium ion cells and batteries shall be manufactured under a quality management program and this requirement is adopted by IMDG Code and ICAO TI/IATA DGR.

The following list is intended to assist the user to identify the main changes introduced in this edition and must not be considered an exhaustive listing. The changes have been prefaced by the section or subsection in which the change occurs.

Shipping Name (UN Number):

UN3480 or UN3481

Hazard Classification:

Class 9 (Miscellaneous)

Organizations governing the transport of lithium batteries are as follows:

AREA	METHOD	ORGANIZATION	PACKING INSTRUCTION OR SPECIAL PROVISION
International	AIR	IATA, ICAO	PI 965-967
International	Maritime	IMDG	Amdt 42-24
International	Rail	RID	
USA	Air, Rail, Road, Maritime	DOT	49 CFR Section 173.185
Europe	Road	ADR	ADR

Material Safety Data Sheet

PST.5000

Cells and batteries must be packed in inner packaging that completely encloses the cell or battery. Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit. Each consignment must be accompanied with a document such as an air waybill with an indication that:

- the package contains lithium ion cells or batteries;
- the package must be handled with care, and that a flammability hazard exists if the package is damaged;
- special procedures should be followed in the event the package is damaged, to include inspection and repacking if necessary; and
- a telephone number for additional information.

Each package must be labelled with a lithium battery handling label; Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

SECTION 15: Regulatory information

Special requirement be according to the local regulations.

《Dangerous Goods Regulations》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods 》

《Occupational Safety and Health Act 》 (OSHA)

《Toxic Substance Control Act》 (TSCA)

《Consumer Product Safety Act 》 (CPSA)

《Federal Environmental Pollution Control Act》 (FEPCA)

《The Oil Pollution Act》 (OPA)

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313) 》 (SARA)

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》 (CWA)

《California Proposition 65》

《Code of Federal Regulations》 (CFR)

《2020 Lithium battery guidance document, revision 1》

Material Safety Data Sheet

PST.5000



SECTION 16: Other information

Note this sheet is provided as technical information only. The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. The supplier makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

End of MSDS